



SAFETY DATA SHEET

INSULATING FIRE BRICK

Section 1 - IDENTIFICATION

GHS product identifier: Insulating Fire Brick - All Grades

Other means of Identification: Insulating Fire Brick, IFB Refractory Brick

Product type: IFB

Relevant identified uses of the substance or mixture and uses advised against:

Identified uses: Refractory lining, back-up insulation

Uses advised against: None known

Supplier: Ceramaterials
525 Silver Lake Road
Dingmans Ferry PA, 18328

Emergency Telephone Number: CHEMTREC - 800-424-9300 or 703-741-5970 (Outside USA and Canada-collect calls accepted). 24 Hour service)

Section 2 - HAZARDS IDENTIFICATION

OSHA/HCS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).


Classification of the substance or mixture: CARCINOGENICITY - Category 1A
SPECIFIC TARGET ORGAN TOXICITY (STOT) REPEATED EXPOSURE-CATEGORY
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 0%

GHS label element Hazard statements:



Signal word: Danger

Hazard statements: If dust is present:
Causes damage to lungs through prolonged or repeated exposure. May cause cancer



Precautionary statements:

Prevention: If dust is present:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves, protective clothing, eye protection, face protection
Do not breathe dust.
Wash thoroughly after handling.
Do not eat, drink, or smoke while using the product.

Response: If exposed, concerned, or feel unwell: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents and container in accordance with all local, regional, national and international regulations

Supplementary Information: Use precautions if exposure exceeds the established OSHA limits.
This material does not present a hazard unless dust is generated from cutting, grinding, or other operations

Hazards not otherwise Classified: None known

Section 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Substance or mixture: Mixture

Other means of identification: Insulating Fire Brick, IFB

CAS number/other identifiers:

CAS NUMBER: Mixture

PRODUCT CODE: Insulating Fire Brick

Ingredient Name	CAS number	%
Ceramic Mix	Proprietary	60 - 98
Product contains:		
Crystalline Silica	13808-60-7	0.1 - 46
Crystalline Silica (cristobalite)	14464-46-1	0.1 - 22

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.



Section 4 - FIRST AID MEASURES

Description of necessary first aid measures:

- Inhalation:** Remove victim to fresh air.
Drink plenty of water and blow nose to evacuate remaining dust.
If coughing or irritation persist seek medical attention.
- Eye contact:** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids.
Check for and remove any contact lenses.
Rinse for at least 15 minutes.
If irritation persists seek medical attention.
- Skin contact:** Gently wash with plenty of soap and water.
If irritation persists seek medical attention.
- Ingestion:** Emergency procedures not normally required.
If prolonged irritation to gastrointestinal tract or mouth persist seek medical attention.

Most important symptoms/effects, acute and delayed Potential acute health effects

- Inhalation:** Respirable airborne particles may cause temporary irritation to the lungs and upper respiratory system.
- Skin contact:** Prolonged exposure may cause dryness or irritation to the skin.
- Eye contact:** Prolonged exposure may cause dryness or irritation to the skin.
- Ingestion:** May cause irritation to gastrointestinal tract or mouth.

Over-exposure signs/symptoms

- Inhalation:** Adverse symptoms may include the following: Irritation
- Eye contact:** Adverse symptoms may include the following: Irritation, Dryness
- Skin contact:** Adverse symptoms may include the following: Irritation, Dryness
- Ingestion:** Adverse symptoms may include the following: Irritation, Stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician:** Medical conditions which may be aggravated by exposure include dryskin, dermatitis, and pre-existing lung conditions such as bronchitis, emphysema, and asthma.
- Specific treatments:** No specific treatment



Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. Wear a suitable NIOSH-Approved dust mask if airborne dust present. Wash contaminated clothing before re-use.

Section 5 - FIRE FIGHTING MEASURES

Specific hazards arising from chemical: None known other than those represented elsewhere in the SDS.

Hazardous thermal decomposition products: Decomposition products may include the following materials:
• Crystalline Silica
During initial exposure to service temperatures, smoke may be emitted which can cause transitory irritation to the lungs and upper respiratory system.

Special protective actions for firefighters: Material will not burn.
Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
No action shall be taken involving any personal risk or without suitable training.
No special firefighting equipment is necessary.

Special protective equipment for fire-fighters: Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency Personnel: No action shall be taken involving any personal risk or without suitable training.
Evacuate surrounding areas.
Keep unnecessary and unprotected personnel from entering.
Provide adequate ventilation.
Wear appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".



Environmental precautions: This material does not pose a significant threat to the environment. Avoid dispersion of material and runoff and contact with waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, or air)

Methods and materials for containment and cleaning up

Small spill: Stop source of spill.
Avoid creating airborne dust.
Use dust suppressant as necessary.
Place material into closed waste disposal container.
Any sweeper or vacuum should be equipped with High Efficiency Particulate (HEPA) filter. Dispose of using a licensed waste disposal contractor.

Large spill: Stop source of spill.
Avoid creating airborne dust.
Use dust suppressant as necessary.
Place material into closed waste disposal container.
Any sweeper or vacuum should be equipped with High Efficiency Particulate (HEPA) filter.
Dispose of using a licensed waste disposal contractor.
Note: See section 1 for emergency contact information and Section 13 for waste disposal.

Section 7 - HANDLING AND STORAGE

Protective measures for safe handling

Protective Measures: Minimize dust generation.
Use appropriate respiratory protection if dust is present above the established exposure limits.
If dusty conditions exist (such as during cutting, sanding, or milling) use engineering controls and/or respiratory protection (see section 8)

Advice on general Occupational hygiene: Eating and smoking should be prohibited in areas where this material is handled, stored and processed.
Workers should wash hands and face before eating and smoking.
Remove contaminated clothing and protective equipment before entering eating areas. See also section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities: Store in accordance with local regulations



Store in original container in a dry area, away from incompatible materials (see Section 10) and food and drink.

Section 8 - Exposure Controls/Personal Protection

Occupational exposure limits:

US Occupational Safety and Health Administration Permissible Exposure Limit (OSHA PEL):

Irritant (Nuisance) Dust:	5mg/m ³
Crystalline Silica (Respirable):	$\frac{10 \text{ mg/m}^3}{\%SiO^2 + 2}$
Crystalline Silica (Total Dust):	$\frac{30 \text{ mg/m}^3}{\%SiO^2 + 2}$

(See 29 CFR 1910.1000 Table Z-3)

American Conference of Governmental and Industrial Hygienists Threshold Limit Value (ACGIH TLV)

Irritant (Nuisance) Dust:	3mg/m ³
Crystalline Silica:	0.025 mg/m ³

Note: TLV and PEL values are for eight hour exposures, unless noted.

Appropriate Engineering controls:

If users operations generate dust, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Power equipment should be fitted with properly designed dust collection device.

Environmental Exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures:

Hygiene Measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that the eyewash stations and safety showers are close to the workstation location



- Respiratory Protection:** Wear a NIOSH-approved dust mask to limit exposure to product dust. Higher dust levels may require use of a half or full mask respirator with dust filters. Use local exhaust if necessary to lower dust levels. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Eye/Face Protection:** Wear safety glasses with side shields or goggles complying with an approved standard to avoid exposure to dust.
- Hand Protection:** Protection Protective gloves should be worn when handling and to avoid abrasion or drying of skin.
- Body Protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved.
- Other Skin Protection:** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved.

Section 9 - Physical and Chemical Properties

Appearance:

Physical State	Solid Blocks of various size
Color	Off-white to gray
Odor	None
Odor Threshold	Not applicable
pH	Not applicable
Melting Point	>2300°F (1260°C)
Boiling Point	N/A
Flash Point	None
Burning Time	Not applicable
Specific Gravity	1.5 - 1.7
Burning Rate	Not applicable
Evaporation Rate	0 (butyl acetate = 1)
Flammability (solid, gas)	Not applicable
Lower Explosive (flammable) Limit	Not available
Upper Explosive (flammable) Limit	Not available
Vapor Pressure	Not applicable
Vapor Density	Not applicable
Relative Density	Not available
Solubility	Insoluble
Solubility in water	Insoluble
Partition coefficient: n-octanol/water	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
SADT	Not available
Viscosity	Not available



Section 10 - STABILITY AND REACTIVITY

Reactivity: This product is normally not reactive.

Chemical stability: This product is stable

Possibility of Hazardous Reactions: Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to Avoid: Avoid strong acids and ammonium salts. Contact with strong oxidizing agents (fluorine, chlorine trifluoride) may present a fire hazard.

Incompatible Materials: Reactive or incompatible with the following materials:
Hydrofluoric acid, fluorine, chlorine trifluoride, oxygen difluoride

Hazardous Decomposition Products: Crystalline silica will dissolve in hydrofluoric acid and produce silicon tetrafluoride, a corrosive gas.

Section 11 - TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
None Known	--	--	--	--
	--	--	--	--

Irritation/Corrosion: Not available

Sensitization: Not available

Mutagenicity: Not available

Carcinogenicity: Not available

Reproductive Toxicity: Not available

Teratogenicity: Not available

Specific Target organ Toxicity: Not available
(single exposure)



Specific target organ toxicity (repeated exposure): This material contains Crystalline Silica, which is known to cause silicosis. silicosis is a rapidly progressive, non-cancerous lung disease that is often fatal

Aspiration hazard: Not available

Information on the likely routes of exposure: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects:

Inhalation: Respirable airborne particles may cause temporary irritation to the lungs and upper respiratory system.

Skin contact: Prolonged exposure may cause dryness or irritatio to the skin.

Eye contact: Will cause mechanical irritation to the eyes. May cause moderate to severe eye irritation and dryness.

Ingestion: May cause irritation to gastrointestinal tract or mouth.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: Adverse symptoms may include the following:
• Irritation

Eye contact: Adverse symptoms may include the following:
• Irritation
• Dryness

Skin contact: Adverse symptoms may include the following:
• Irritation
• Dryness

Ingestion: Adverse symptoms may include the following:
• Irritation
• Stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects: Not available.

Potential delayed effects: Not available.



Long term exposure

Potential immediate effects: Not available.

Potential delayed effects: Not available.

Potential chronic health effects: Not available.

General: No other known significant effects or critical hazards.

Carcinogenicity: Crystalline silica - long term overexposure may cause permanent and irreversible lung damage, including silicosis, and increase the risk of lung cancer, kidney, and liver damage. Silicosis is a rapidly progressive, non-cancerous lung disease that is often fatal.

IARC(International Agency for Research on Cancer): 014808-60-7 Silica dust, crystalline, in the form of quartz or cristobalite - Group 1 (Sup 7, 68,100C,2012)

National Toxicology Program (NTP) Report on Carcinogens: Silica, Crystalline(Respirable Size) - Known To Be Human Carcinogen

OSHA: Crystalline Silica classified as a Category 1A Carcinogen

Mutagenicity: No other known significant effects or critical hazards.

Teratogenicity: No other known significant effects or critical hazards.

Developmental: No other known significant effects or critical hazards.

Fertility effects: No other known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates: No other known significant effects or critical hazards.

Section 12 - Ecological Information

Toxicity: Not Available

Persistence and Degradability: Not Available

Bioaccumulative Potential: Not Available

**Mobility in soil
Soil/water partition
Coefficient (Koc):** Not Available

Other adverse effects: Most of the ingredients in this product are naturally occurring minerals, and, unless contaminated in service, are not hazardous to the environment.



Section 13 - Disposal Considerations

Disposal methods:

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

This material and its container must be disposed of in a safe way.

Care should be taken when handling emptied containers that have not been cleaned or rinsed out.

Empty containers or liners may retain some product residues.

Avoid dispersal of spilled material and runoff and contact with waterways, drains and sewers.

Section 14 - Transport Information

Table with 5 columns: --, DOT Classification, TDG Classification, IMDG, IATA. Row 1: UN number, Not Regulated, Not Regulated, Not Regulated, Not Regulated

Special precautions for user:

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15 - REGULATORY INFORMATION

U.S. Federal regulations:

TSCA 8(a) CDR Exempt/Partial exemption: Not applicable

United States Inventory (TSCA 8b): This material is listed.

Clean Air Act Section 112

(b) Hazardous Air

Pollutants (HAPs): Not listed



Clean Air Act Section 602

Class I Substances: Not listed

Clean Air Act Section 602

Class II Substances: Not listed

DEA List I Chemicals

(Precursor Chemicals): Not listed

DEA List II Chemicals

(Essential Chemicals): Not listed

SARA 302/304

Composition/Information on ingredients: No products were found

SARA 304 RQ: Not applicable

SARA 311/312

Classification:

Composition/information on ingredients:

Name	%	Immediate (acute) Health Hazard	Delayed (chronic) Health Hazard	Fire Hazard	Reactivity Hazard	Sudden Release of Pressure
Ceramic Matrix	60 - 98	No	No	No	No	No
Crystalline Silica (Quartz)	0.1 - 46	Yes	Yes	No	No	No
Crystalline Silica (cristobalite)	0.1 - 22	Yes	Yes	No	No	No

Section 313 listed: No

Section 313 listed: Not applicable

State regulations:

New York: Crystalline Silica

New Jersey: Crystalline Silica

Pennsylvania: Crystalline Silica

Massachusetts: Crystalline Silica

Rhode Island: Crystalline Silica

California Prop. 65: Crystalline Silica

International Lists

DSL (Canada): All ingredients are listed, or exempt from inclusion, on the Canadian Domestic Substances List (DSL).



Canada Inventory (WHMIS): Listed. Class D-2A: Material causing other toxic effects. Very Toxic - Chronic.

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.



- Australia inventory (AICS):** Not determined.
- China inventory (IECSC):** Not determined.
- Japan inventory:** Not determined.
- Korea inventory:** Not determined.
- Malaysia Inventory (EHS Register):** Not determined.
- New Zealand Inventory of Chemicals (NZIoC):** Not determined.
- Philippines inventory (PICCS):** Not determined.
- Taiwan inventory (CSNN):** Not determined.

- Chemical Weapons Convention List Schedule I Chemicals:** Not Listed
- Chemical Weapons Convention List Schedule II Chemicals:** Not Listed
- Chemical Weapons Convention List Schedule III Chemicals:** Not Listed

DSCI (Europe): R48/20: Harmful - Danger of serious damage to health by prolonged exposure through inhalation.
 R36: Irritating to the eyes
 R39: Danger of serious irreversible side effects.
 R45: May cause cancer.

Section 16 - Other Information

Hazardous Material Information System (U.S.A.)


Health	2
Flammability	0
Physical Hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.



National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright © 1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety. Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

DISCLAIMER – CeraMaterials, believes the information contained in this Safety Data Sheet (SDS) to be accurate and reliable as of the date of issue, and is provided in good faith as a service to our customers and to comply with applicable laws. This document is intended as a guide for the safe handling, storage, and use of this material under normal conditions of use. No representation, warranty, or guarantee, either express or implied, is intended or given. CeraMaterials does not accept any liability for any loss, injury, or damage resulting from the use of this product.

History

Date of issue/Date of revision: June 1, 2015
Date of previous issue: Version: May 22, 2014
Changes: 2